

United Payments

Verifone VX 675



0333 567 4 568



support@unitedpayments.co.uk



www.unitedpayments.co.uk



Verifone VX 675

Verifone's VX 675 is the world's smallest, all-in-one, wireless hand-held payment device, ergonomically designed to fit comfortably in the palm of your hand. Incredibly advanced, sleek and elegant, the VX 675 is ideal for pay-anywhere, anytime environments.

- The smallest, full-function, portable device on the market
- Enables long-range wireless payments for retailers on the go
- EMV Level 1 and 2 Type approvals, PCI PTS 3.0 approved, offering the best security

Specifications

Processor

400 MHz, ARM11 32-bit RISC processor

Memory

192 MB (128 MB Flash, 64 MB SDRAM)

Display

2.8" QVGA

Connectivity

HSPA + 3G radio, 2.4GHz WiFi, Bluetooth 2.1

Printer

30 lps, 40 mm paper roll

Contactless

ISO14443 A&B, MiFare, ISO18092 capable, EMVCo L1 certification, supports major NFC/contactless schemes

Other Standard Features

2 SAM slots

Base

USB base: USB host/device connector and integrated charging

Full-feature base: Dial-up, Ethernet, RS-232, USB host/device connector, integrated charging

Bluetooth base: Dial-up, Ethernet, Bluetooth support, integrated charging

Card Readers

Triple track MSR, landed smart card

Power

Voltage: AC input 100-240 VAC, 50/60 Hz; DC output 5 VDC, 1A

Environmental

Operating temperature: 0° to 50° C (32° to 122° F); storage temperature: -20° to 60° C (-4° to 140° F); relative humidity: 5% to 90%, non-condensing

Physical

Terminal: 163 mm L x 78 mm W x 52 mm H
Base: 131 mm L x 84 mm W x 42 mm H

	VX 675 GPRS	VX 675 WF/BT	VX 675 3G
Terminal Connectivity	GSM/GPRS 850/900/1800/1900 MHz	WiFi 802.11b/g/n, Bluetooth local area	WiFi 802.11b/g/n, Bluetooth local area
Contactless	Optional	Standard	Standard
GPS	-	-	Standard
Peripheral Ports	USB device support, integrated charging	USB host and device support, integrated charging	USB host and device support, integrated charging
Dual SIM	-	-	Standard
Micro-SD	-	Standard	Standard
Battery	Li-Ion 3.6V/2200mAh	Li-Ion 3.7V/2450mAh	Li-Ion 3.7V/2450mAh
Weight	Terminal: 336g; full shipping: 647g	Terminal: 337g; full shipping: 732g	Terminal: 345g; full shipping: 736g